



# CONCRETE CRACK FILLER

◆ The Pro's Choice Since 1936



Sakrete® Concrete Crack Filler is a ready to use, polymer based repair material designed to fill and seal cracks in concrete.

## Features:

- Fills cracks in concrete up to 1/2" (12 mm) wide and 1/4" (6 mm) deep
- Interior/Exterior
- Protects from water penetration
- Can be painted with a latex based paint
- Ready to use

## Use For:

- Driveways
- Walkways
- Patios
- Slabs

## Yield/Water/Coverage:

Container Size	Yield/Coverage
1 quart (.95 L)	Will fill approximately 35 ft (10.6 m) of a 1/4" (6 mm) deep by 1/2" (12 mm) wide crack

NOTE: The yield is approximate and does not allow for waste and spillage.

DIVISION 3

Common Work Results for Concrete - 03 05 00

**Color:** Gray

## Preparation/Application:

For best results all materials should be stored between 40°F (4°C) and 80°F (27°C) 24 hours prior to installation.

1. Do not apply when temperatures are expected to fall below 50°F (10°C) within 24 hours.
2. Clean area and remove all loose concrete, grease, oil, paint, dirt and any foreign materials that will inhibit performance.

## Use:

1. Shake vigorously before using.
2. Cut applicator tip to size needed for the repair.
3. Squeeze Crack Filler into the cracks. Sand can be added to the crack up to 1/4" (6 mm) below the surface before applying Sakrete Concrete Crack Filler.

4. Troweling is not necessary.
5. Deep cracks may require more than one application due to shrinkage during curing.
6. Allow to dry overnight between applications.
7. Maximum crack width of 1/2" (12 mm) and maximum depth of 1/4" (6 mm). Width to depth ratio should be 2 to 1.

## Curing:

1. Protect from rain and water for a minimum of 24 hours. Thicker applications may require more time to dry.
2. DO NOT APPLY any portland cement-based products over Sakrete Crack Filler.

## Precautions:

Air, mix and substrate temperatures should be between 50°F (10°C) and 90°F (32°C) and no rain in the forecast within 24 hours of application. For applications outside this range of temperatures and conditions, contact Sakrete Technical Service.

- Colder temperatures or higher humidity conditions will retard set times.
- Use only clean container and tools.
- Protect from freezing for 48 hours

NOTE: *Proper application and installation of all Sakrete products are the responsibility of the end user.*

## Safety:

READ and UNDERSTAND the Safety Data Sheet (SDS) before using this product. WARNING: Wear protective clothing and equipment. For emergency information, call CHEMTREC at 800-424-9300 or 703-527-3887 (outside USA).

**KEEP OUT OF REACH OF CHILDREN.**

## Limited Product Warranty:

The manufacturer warrants that this product shall be of merchantable quality when used or applied in accordance with the manufacturer's instructions. This product is not warranted as suitable for any purpose other than the general purpose for which it is intended. This warranty runs for one (1) year from the dates the product is purchased. ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ON THIS PRODUCT IS LIMITED TO THE DURATION OF THIS WARRANTY. Liability under this warranty is limited to replacement or defective products or, at the manufacturer's option, refund of the purchase price. CONSEQUENTIAL AND INCIDENTAL DAMAGES ARE NOT RECOVERABLE UNDER THIS WARRANTY.



SAKRETE® and the background design are registered trademarks of SAKRETE of North America LLC, Charlotte, NC 28217 • ©2006. SAKRETE® is manufactured under license from SAKRETE of North America LLC. For current and complete product information, contact SAKRETE Technical Services toll-free at 866-725-7383 or visit Sakrete.com.