



FENCE POST MIX

◆ The Pro's Choice Since 1936



Sakrete® Fence Post Mix is a mixture of sand, coarse aggregate and cementitious materials. For fence post installations only.

Features:

- Ideal for fence post projects
- No mixing required

Use For:

- Setting fence posts

Yield/Water/Coverage:

Bag Size	Yield	Water
80 lb (36.3 kg)	0.6 ft ³ (0.02 m ³)	As needed alternately with dry material

NOTE: Yield and water are approximate.

Post Setting - Based on average 10" diameter hole:

12" Deep	18" Deep	24" Deep	30" Deep
1.25 bags	2 bags	2.5 bags	3 bags

For information on the number of bags needed for any combination of hole or post size, visit Sakrete.com and use the Calculator.

Technical Support:

Compressive Strength:
2,500 psi (17 MPa)

Colors:

Gray

Preparation/Application:

For best results all materials should be stored between 40°F (4°C) and 80°F (27°C) 24 hours prior to installation.

Post and Poles Placement:

1. Dig hole to required depth and diameter (depth should be 1/3" the length of the post or pole and hole should be 3 times the diameter of the pole or post width). Place 4" (102 mm) to 6" (152 mm) of gravel as a base and compact.
2. Place the post or pole in the center of the hole and onto the gravel base.
3. Level and support post or pole in place
4. Fill hole with 1/3 full of water then add concrete directly from bag.
5. Continue placing alternately water and concrete into hole until full.

6. Rod material in hole to assist in getting a good mix.
7. If surface is dry add more water. Excess surface water is not a problem.
8. Re-check the level of the post.
9. Slope top of mix to allow water to drain away.

Refer to:

- ACI 305R Guide to Hot Weather Concreting
- ACI 306R Guide to Cold Weather Concreting

Curing:

No special curing required.

Precautions:

Air, mix and substrate temperatures should be between 40°F (4°C) and 90°F (32°C) in the forecast within 24 hours of application. For applications outside this range of temperatures and conditions, contact Sakrete Technical Service.

- Colder temperatures or higher humidity conditions will retard set times
- Do not add any materials other than clean potable water..
- Protect from freezing for 48 hours.

NOTE: Proper application and installation of all Sakrete products are the responsibility of the end user.

Safety:

READ and UNDERSTAND the Safety Data Sheet (SDS) before using this product. WARNING: Wear protective clothing and equipment. For emergency information, call CHEMTREC at 800-424-9300 or 703-527-3887 (outside USA).

KEEP OUT OF REACH OF CHILDREN.

Limited Product Warranty:

The manufacturer warrants that this product shall be of merchantable quality when used or applied in accordance with the manufacturer's instructions. This product is not warranted as suitable for any purpose other than the general purpose for which it is intended. This warranty runs for one (1) year from the dates the product is purchased. ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ON THIS PRODUCT IS LIMITED TO THE DURATION OF THIS WARRANTY. Liability under this warranty is limited to replacement or defective products or, at the manufacturer's option, refund of the purchase price. CONSEQUENTIAL AND INCIDENTAL DAMAGES ARE NOT RECOVERABLE UNDER THIS WARRANTY.