



MORTAR REPAIR

◆ The Pro's Choice Since 1936



Sakrete® Mortar Repair is a siliconized acrylic latex for repairing deteriorated mortar joints and cracks in concrete and masonry walls.

Features:

- Weather resistant - fills and seals joints or cracks
- Paintable after curing
- Sand textured look

Use For:

- Replacing deteriorated or missing mortar from joints in brick or block
- Repairing cracks in concrete or masonry walls

Yield/Coverage:

Tube Size	Yield
10.3 fl oz tube (304 mL)	3/8" (9.5 mm) x 12 ft (3.7 m) long

Technical Data:

DIVISION 7
Joint sealants - 07 92 00

Color:

Gray

Preparation/Application:

For best results all materials should be stored between 50°F (10°C) and 80°F (27°C) 24 hours prior to installation.

1. Remove all loose mortar from joints.
2. Spray joints with water to ensure all dust and dirt has been removed. Allow to dry.
3. Cut nozzle to desire bead width (a typical mortar joint is 3/8" (9.5 mm)) and puncture seal at the inside base of the tip.
4. Squeeze Mortar Repair into joints using a standard caulking gun.
5. Smooth and trim excess caulk with a moist putty knife or jointing tool.

Clean up:

Cleans up with water prior to drying.

Precautions:

Air, mix and substrate temperatures should be between 50°F (10°C) and 90°F (32°C) and no rain in the forecast within 24 hours of application.

- Colder temperatures or higher humidity conditions will retard set times
- Use only clean tools.
- Protect from freezing for 48 hours.

NOTE: Proper application and installation of all Sakrete products are the responsibility of the end user.

Safety:

READ and UNDERSTAND the Safety Data Sheet (SDS) before using this product. WARNING: Wear protective clothing and equipment. For emergency information, call CHEMTREC at 800-424-9300 or 703-527-3887 (outside USA).

KEEP OUT OF REACH OF CHILDREN.

Limited Product Warranty:

The manufacturer warrants that this product shall be of merchantable quality when used or applied in accordance with the manufacturer's instructions. This product is not warranted as suitable for any purpose other than the general purpose for which it is intended. This warranty runs for one (1) year from the dates the product is purchased. ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ON THIS PRODUCT IS LIMITED TO THE DURATION OF THIS WARRANTY. Liability under this warranty is limited to replacement or defective products or, at the manufacturer's option, refund of the purchase price. CONSEQUENTIAL AND INCIDENTAL DAMAGES ARE NOT RECOVERABLE UNDER THIS WARRANTY.